


acrobat mini | trim short

We aim to create cleaner ceilings.
Show what you want, hide what you need.



luminaire specs	3
configure yours	4
finishes	5
luminaire output	6
accessories	8
housing	10
drivers	12



acrobat mini | trim short

installation

luminaire specs			
delivered lumen	up to 700lm		
watts	up to 8.9W		
efficacy	101lm/W		
CRI	90+	97	
R9 value	CRI 90+: >50	CRI 97: >91	
CBCP	10° pc: 6731cd	20° pc: 4655cd	
	40° pc: 1373cd	60° pc: 627cd	
	40° glass: 2036cd		
color temperature (CCT)	2700K	3000K	3500K
	dim 2 warm: 3000K > 1800K		
color consistency	2-step SDCM		
driver input voltage	120V		
dimming	DALI/0-10V/phase dimming		
power supply	constant current driver with +.9 power		
	factor and +80% efficiency		
optics	10° / 20° / 40° / 60°		
adjustability	rotation 360°	tilt 60°	
suitable for	dry locations (IP20)		
ceiling appearance	trim		

drill holze size	Ø2-2/3" (Ø68 mm)	
ceiling thickness	min. 5/64" (2 mm)	max. 15/16" (24 mm)
L80	>55000 h	
housing (not incl.)	IC box airtight	IC box non-airtight
	non-IC frame	remodeling box
double springs (not incl.)	10 pack (5 sets)	
material	aluminum	brass
aluminum finishes	black ano	white struc
	brushed steel	brushed grey
	brushed bronze	
aluminum weight	0.80 lb (0.36 kg)	
brass finishes	brushed nickel	light bronze
	dark bronze	canon de fusil dark
	canon de fusil light	
brass weight	1.19 lb (0.54 kg)	
general listings	UL Listed	California Title 24
warranty	1 year (5 years on LED)	

Respect distances, cable sections and IP ratings.
Split AC and DC to prevent LED glowing.

configure yours

21032

--

product		variant		CRI		CCT *		beam		dimming **		finish			
21032.	acrobat mini trim	05.	short alu	1	90+	01.	2700K	03	20° pc	0.	driver excluded	001	black ano		
						02.	3000K	06	40° pc			002	white struc		
						03.	3500K	07	40° glass			003	brushed steel		
								09	60° pc			004	brushed grey		
												005	brushed bronze		
						90.	dim 2 warm	07	40° glass	0.	driver excluded	001	black ano		
												002	white struc		
												003	brushed steel		
												004	brushed grey		
												005	brushed bronze		
				08.	short brass	1	90+	90.	dim 2 warm	07	40° glass	0.	driver excluded	701	brushed nickel
														702	light bronze
														703	dark bronze
														704	canon de fusil dark
														705	canon de fusil light
				2		97	01.	2700K	01	10° pc	0.	driver excluded	701	brushed nickel	
02.	3000K						03	20° pc	702	light bronze					
03.	3500K						06	40° pc	703	dark bronze					
							07	40° glass	704	canon de fusil dark					
							09	60° pc	705	canon de fusil light					

* other CCT available on request

** phase dimming, 0-10V & dali possible, consult driver matrix, driver sold separately

driver matrix

finishes

aluminum finishes

white struc (RAL 9003)



brushed steel



brushed bronze



brushed grey



black ano



custom brass finishes

brushed nickel



light bronze



dark bronze



canon de fusil light




canon de fusil dark




Custom RAL and brass finishes available on request.

correlated color temperature (CCT)


2700K: extra warm white




3000K: warm white




3500K: neutral white




dim 2 warm: 3000K > 1800K




beam angle							
		10° pc	20° pc	40° pc	60° pc	40° glass	dim 2 warm (40° glass)
short alu		350mA max	350mA max	350mA max	350mA max	500mA max	350mA max
short brass		350mA max	350mA max	350mA max	350mA max	500mA max	350mA max
luminaire output							
		350mA		500mA			
		(6.6W, 19.9Vf)	(6.4W, 18.3Vf)	(6.0W, 17.1Vf)	(8.9W, 17.8Vf)		
2700K	10° pc	475lm	-	-	-		
	20° pc	-	550lm	-	-		
	40° pc	-	550lm	-	-		
	60° pc	-	500lm	-	-		
	40° glass	-	-	475lm	650lm		
3000K	10° pc	500lm	-	-	-		
	20° pc	-	575lm	-	-		
	40° pc	-	575lm	-	-		
	60° pc	-	525lm	-	-		
	40° glass	-	-	500lm	675lm		
3500K	10° pc	525lm	-	-	-		
	20° pc	-	600lm	-	-		
	40° pc	-	600lm	-	-		
	60° pc	-	550lm	-	-		
	40° glass	-	-	525lm	700lm		
dim 2 warm	40° glass	-	-	425lm	-		




10° pc




20° pc




40° pc




60° pc



40° glass





dim 2 warm (40° glass)




accessories				
optional double springs (not incl.)				
				product code
double springs - 10 pack (5 sets)				8000-8480
housing (not incl.)				
			UL listed	product code
IC box + plaster frame 3-1/2” high airtight			yes	9000-0107
IC box + plaster frame 3-1/2” high non-airtight			yes	9000-0101
IC box + plaster frame 2-1/4” high airtight			yes	9000-0108
IC box + plaster frame 2-1/4” high non-airtight			yes	9000-0103
NON-IC plaster frame			yes	9000-0106
remodeling box 2.37×1.5×8			yes	9000-0104
bar hanger kit			n/a	9000-0102
drivers (not incl.)				
	number of fixtures	Title 24 JA8 compliant	UL listed	product code
SOLOdrive 0-10V 350mA 22W	1-2	yes	yes	9000-1008
SOLOdrive 0-10V 500mA 22W	1-2	yes	yes	9000-1002
SOLOdrive DALI 350mA 22W	1-2	yes	yes	9000-1006
SOLOdrive DALI 500mA 22W	1-2	yes	yes	9000-1001
Phase dimming / 0-10V dimmable driver constant current 350mA 15W	1	yes	yes	9000-1028
Phase dimming / 0-10V dimmable driver constant current 500mA 15W	1	yes	yes	9000-1029
DALI / 0-10V dimmable driver 60W constant current multi power	2-4	no	yes	9000-1014

optional double springs (not incl.)		
	product code	ceiling type
double springs - 10 pack (5 sets)	8000-8480	wood / concrete / thicker than 24 mm

replacing single springs to double springs



housing (not incl.)



IC box + plaster frame 3-1/2" high


[spec sheet](#)

new construction airtight / non-airtight

for use insulated ceiling

UL listed

dimensions D x W x H 12-7/16 x 8-9/16 x 3-7/16"



IC box + plaster frame 2-1/4" high


[spec sheet](#)

new construction airtight / non-airtight

for use insulated ceiling

UL listed

dimensions D x W x H 12-7/16 x 8-9/16 x 2-3/10"



non-IC plaster frame


[spec sheet](#)

new construction

for use in non-insulated ceiling

UL listed

dimensions D x W x H 15 x 8-9/16 x 4-3/8"



remodeling box 2.37x1.5x8

[spec sheet](#)


for remote installation

UL listed

does not fit through hole

dimensions D x W x H 8 x 2-9/16 x 1-2/3"

illustration in combination with IC box



driver matrix

new construction	insulated ceiling	IC box + plaster frame 3-1/2"	remote driver	remodeling box 2.37x1.5x8
			local driver	driver in inner junction box
		IC box + plaster frame 2-1/4"	remote driver	remodeling box 2.37x1.5x8
			local driver	driver in inner junction box
	non-insulated ceiling	non-IC plaster frame	remote driver	remodeling box 2.37x1.5x8
			local driver	driver in inner junction box
remodeling		remote driver	remodeling box 2.37x1.5x8	

driver matrix

cable length

compatible drivers (not incl.)

remodeling box 2.37x1.5x8 / integral driver box
SOLOdrive 0-10V 350mA 22W
SOLOdrive 0-10V 500mA 22W
SOLOdrive DALI 350mA 22W
SOLOdrive DALI 500mA 22W
Phase dimming / 0-10V dimmable driver constant current 350mA 15W
Phase dimming / 0-10V dimmable driver constant current 500mA 15W


illustration driver matrix

local driver

above ceiling access required for both installation and service ¹


check driver matrix (cut-out column) ²

² remodel




driver matrix


¹ new construction
non-IC



¹ new construction
IC 2-1/4"




¹ new construction
IC 3-1/2"




remote driver ³


remodel




new construction
non-IC



new construction
IC 2-1/4"



new construction
IC 3-1/2"



³ max driver distance

AWG18 (2 × 1 mm ²)	40 ft (12 m)
AWG16 (2 × 1.5 mm ²)	65 ft (20 m)
AWG14 (2 × 2.5 mm ²)	100 ft (30 m)
AWG12 (2 × 4 mm ²)	160 ft (49 m)

wiring diagram

serial connection

